EN

Sepaks ST 110

Products > Construction Chemicals > Formwork Oils

Sepaks ST 110 is a ready-to-use formwork release agent that facilitates the easy removal of concrete from steel molds and provides a smooth, stain-free surface to the concrete

■ Fields of Application

- Steel Molds – Tunnel Molds
- Plywood Formwork (Optional)

■ Advantages

- Ensures easy and smooth removal of molds
- Helps in cleaning molds and reduces the need for frequent cleaning
- Provides a smoother concrete surface
- Does not leave stains or dirt on the concrete
- Extends the lifespan of the mold and provides cost savings in overall expenses

1 Application

Formwork surfaces must be free from mortar residues and slurry. Sepaks ST 110 can be applied using a stiff brush, roller, or sprayer. After application, it is necessary to protect the molds from rain for the first few hours.

2 Consumption

1 L, 25-30 m^2 (Roller)

3 Storage Life

In a sealed container and protected from frost, the product has a minimum shelf life of 12 months.

4 Packaging

Plastic container 200-liter steel drum1000-liter IBC (Intermediate Bulk Container)

5 Precautions

- Sepaks ST 110 must be protected from frost
- If Exposed to Frost: Before use, the product should be brought to room temperature, allowed to self-warm without exposure to fire, and thoroughly mixed
- Additives: It is not recommended to add water or solvents to Sepaks ST 110 before or during use



TECHNICAL DATAS

Appearance	Fluid
Density	(20°C): 0,96 ± 002kg/l
Flash Point	Non-flammable