



# PXIe-7976

## Specifications

Provided by:



Test & Measurement Automation

Embedded Control & Monitoring

Cyth Systems  
9939 Via Pasar  
San Diego, CA 92126

phone (858) 537-1960  
[support@cyth.com](mailto:support@cyth.com)



Authorized  
Distributor



Integration  
Partner

# Contents

PXIe-7976 Specifications .....	3
--------------------------------	---

# PXIe-7976 Specifications

## Definitions

**Warranted** specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

**Characteristics** describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- **Typical** specifications describe the performance met by a majority of models.
- **Nominal** specifications describe an attribute that is based on design, conformance testing, or supplemental testing.

Specifications are **Typical** unless otherwise noted.

## Reconfigurable FPGA

FPGA	Kintex-7 XC7K410T
LUTs	254,200
DSP48 Slices (25 × 18 Multiplier)	1,540
Embedded Block RAM (kbits)	28,620
Default timebase	40 MHz

Timebase reference sources	PXI Express 100 MHz (PXIe_CLK100)
Timebase accuracy	±100 ppm, 250 ps peak-to-peak jitter
Data transfers	DMA, interrupts, programmed I/O
Number of DMA channels	32

## FPGA Digital Input/Output

Number of general-purpose channels	136, configurable as 136 single-ended, 68 differential, or a combination of both <sup>[1]</sup>
<b>Channels per bank</b>	
Bank 0/Bank 1	48
Bank 2	40
Compatibility	Configured through the FPGA and based on the attached adapter module; 1.2 V, 1.5 V, 1.8 V, 2.5 V, and 3.3 V I/O standards (refer to <a href="http://xilinx.com">xilinx.com</a> ).
Protection	Refer to <a href="http://xilinx.com">xilinx.com</a> .
Current	Refer to <a href="http://xilinx.com">xilinx.com</a> .
<b>Maximum I/O data rates</b>	

Single-ended	400 Mb/s
Differential	1 Gb/s for LVDS
Multi-region clock inputs	6
Single-region clock inputs	5
Connection resources	PXI triggers, PXI_CLK10, PXI star trigger, PXIe_DStarA, PXIe_DStarB, PXIe_DStarC, and PXIe_Sync100

## Onboard DRAM

Memory size	2 GB single bank
Theoretical maximum data rate	10.5 GB/s

## Bus Interface

Form factor	x8 PXI Express, specification v2.1 compliant
Slot compatibility	x4, x8, and x16 PXI Express or PXI Express hybrid slots

## Maximum Power Requirements



**Note** Power requirements are dependent on the adapter module and contents of the LabVIEW FPGA VI used in your application.

+3.3 VDC ( $\pm 5\%$ )	3 A
+12 V	3 A

## Physical

Dimensions (not including connectors)	18.8 cm $\times$ 12.9 cm (7.4 in. $\times$ 5.1 in.)
Weight	190 g (6.7 oz)

## Maximum Working Voltage



**Note** Maximum working voltage refers to the signal voltage plus the common-mode voltage.

Channel-to-earth	0 V to 3.3 V, Measurement Category I
Channel-to-channel	0 V to 3.3 V, Measurement Category I



**Caution** Do not use this device for connecting to signals in Measurement Categories II, III, or IV.

# Environment

Maximum altitude	2,000 m (800 mbar) (at 25 °C ambient temperature)
Pollution Degree	2

Indoor use only.

# Operating Environment

Ambient temperature range	0 °C to 55 °C
Relative humidity range	10% to 90%, noncondensing

# Storage Environment

Ambient temperature range	-20 °C to 70 °C
Relative humidity range	5% to 95%, noncondensing

# Shock and Vibration

Operating shock	30 g peak, half-sine, 11 ms pulse
<b>Random vibration</b>	
Operating	5 Hz to 500 Hz, 0.3 grms

Nonoperating

5 Hz to 500 Hz, 2.4 grms

## Compliance and Certifications

### Safety

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA 61010-1



**Note** For UL and other safety certifications, refer to the product label or the [Online Product Certification](#) section.

### Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions
- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



**Note** In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.



**Note** Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



**Note** For EMC declarations, certifications, and additional information, refer to the [Product Certifications and Declarations](#) section.

## Product Certifications and Declarations

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit [ni.com/product-certifications](#), search by model number, and click the appropriate link.

## Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the ***Engineering a Healthy Planet*** web page at [ni.com/environment](#). This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

### EU and UK Customers

- **Waste Electrical and Electronic Equipment (WEEE)**—At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit [ni.com/environment/weee](#).

### 电子信息产品污染控制管理办法（中国RoHS）

- **中国RoHS**—NI符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于NI中国RoHS合规性信息，请登录 [ni.com/environment/rohs\\_china](#)。 (For information about China RoHS compliance, go to [ni.com/](#)

environment/rohs\_china.)